




FILTER or SMOOTHING CHOKE — Shielded Type

“X” type drawn steel cases make this series of chokes desirable for sound equipment, transmitters and electronic equipment. Insulated leads 8" to 10" long. Black wrinkle finish.



Type	Inductance Henrys	Current Ma.	Resistance Ohms	Max. Op. Peak Volts	A	B	D	H	W	Weight Lbs.	Core Size	Code
10-100X	15	100	155	500	2 $\frac{1}{8}$	1 $\frac{3}{4}$	2 $\frac{1}{2}$	3	2 $\frac{1}{2}$	2 $\frac{1}{2}$	1 x 1	Helix
10-150X	10	150	102	600	2 $\frac{1}{2}$	1 $\frac{3}{4}$	3 $\frac{1}{8}$	3 $\frac{3}{4}$	3 $\frac{1}{4}$	4 $\frac{1}{4}$	1 $\frac{1}{4}$ x 1	Hello
5-200X	5	200	65	600	2 $\frac{1}{8}$	1 $\frac{3}{4}$	2 $\frac{1}{2}$	3	2 $\frac{1}{2}$	2 $\frac{1}{2}$	1 x 1	Helid
10-200X	10	200	82	800	2 $\frac{1}{2}$	2 $\frac{1}{4}$	3 $\frac{1}{8}$	3 $\frac{3}{4}$	3 $\frac{3}{4}$	5 $\frac{1}{2}$	1 $\frac{1}{4}$ x 1 $\frac{1}{2}$	Helve
5-300X	5	300	57	1000	2 $\frac{1}{2}$	2 $\frac{1}{4}$	3 $\frac{1}{8}$	3 $\frac{3}{4}$	3 $\frac{3}{4}$	5 $\frac{1}{2}$	1 $\frac{1}{4}$ x 1 $\frac{1}{2}$	Hemab
10-300X	10	300	63	800	3	3	3 $\frac{3}{4}$	4 $\frac{1}{2}$	4 $\frac{1}{2}$	10 $\frac{1}{2}$	1 $\frac{1}{2}$ x 2	Hence
10-500X	10	500	53	1000	4 $\frac{9}{16}$	3 $\frac{3}{4}$	5	6 $\frac{3}{8}$	5 $\frac{1}{2}$	21	2 x 2	Henna
30-65X	30	65	380	500	2 $\frac{1}{8}$	1 $\frac{3}{4}$	2 $\frac{1}{2}$	3	2 $\frac{1}{2}$	2 $\frac{1}{4}$	1 x 1	Henni
30-100X	30	100	280	500	2 $\frac{1}{2}$	2 $\frac{1}{8}$	3 $\frac{1}{8}$	3 $\frac{3}{4}$	3 $\frac{1}{4}$	4 $\frac{3}{4}$	1 $\frac{1}{4}$ x 1 $\frac{1}{4}$	Henry
30-150X	25	150	190	800	3	2 $\frac{1}{2}$	3 $\frac{3}{4}$	4 $\frac{1}{2}$	4	8	1 $\frac{1}{2}$ x 1 $\frac{1}{2}$	Heron
30-200X	26	200	152	800	3	3 $\frac{3}{8}$	3 $\frac{3}{4}$	4 $\frac{1}{2}$	4 $\frac{7}{8}$	11 $\frac{1}{2}$	1 $\frac{1}{2}$ x 2 $\frac{1}{4}$	Hilly
30-300X	30	300	144	1000	4 $\frac{9}{16}$	4	5	6 $\frac{3}{8}$	5 $\frac{3}{4}$	21 $\frac{1}{2}$	2 x 2 $\frac{1}{4}$	Hiltz

“PRODUCTION FACILITIES FOR ONE OR THOUSANDS”